

Pushing the limits of what is possible

Tractus3D T650 Tech Specs

Technology	Fused Deposition Modeling (FDM)
Print head	Dual extrusion printhead optional
Build volume (mm)	170 diameter x 285 height (315 center) / 6,47 liter
XY resolution	0,01mm (10 micron)
Z resolution	0,05mm (50 micron)
Maximum layer thickness	1mm (1000 micron)
Maximum travel speed	600mm/s
Build plate temperature	100 degrees Celsius
Nozzle temperature	300 degrees Celsius
Supported materials	PLA/ABS/PETG/PRO1/NinjaFlex/many more
Filament diameter	1.75mm
Filament out sensor	Yes
Connectivity	LAN (RJ45)
Touch screen	On printer control
Casing	Aluminium with Lexan
Dimensions	32,5cm x 37,5cm x 67,5cm high
Input	100-240 VAC, 24 VDC 12 A, 220 W
Software	Simplify3D
Preferred room temperature	15 – 25 degrees Celsius
Humidity level	30 - 50 %
Environment cleanliness	Medium "office clean"

Tractus3D B.V.
Bernseweg 14
5324 JW AMMERZODEN
Tel: 0418 712052
Email: info@tractus3d.com
KvK 62892460
BTW NL8550.01.446.B01
IBAN NL58RABO0302530371
BIC RABONL2U



SLA (Service Level Agreement) 1 year optional € 700,00 per year

- A one-time extra printhead for free as a spare part
- Free cleaning of dirty printheads (excluding the postal costs for the return-shipment outside The Netherlands)
- 50% discount on all worn parts
- 50% discount on all upgrade parts when a new development on the printer is available
- 20% discount on all filaments